

**EMRA 2006 Season  
- Tech Check List -**

<b>Note: Fairing lowers must be removed prior to Technical Inspection. No exceptions.</b>	
	<b>OK</b>
<b>Fluids</b> <b>Note: The use of antifreeze is strictly prohibited.</b>	
All drain plugs and filler caps (except fuel cap) safety wired	
Oil filter bolt safety wired, oil filter cans safety wired <b>or</b> clamped	
Vent and overflow tubes routed into catch can	
Brake master cylinder taped <b>or</b> wrapped with terry cloth	
<b>Brakes</b>	
Banjo bolts safety wired <b>or</b> siliconed	
Caliper mounting nuts and/or bolts safety wired	
Test lever travel front and rear	
Front brake lever bolt safety wired <b>or</b> siliconed <b>or</b> secured with castellated nut and cotter pin	
<b>Front forks</b>	
Axle nut secured with safety wire or cotter pin. Reusable cotter pins must be safety wired	
Axle pinch bolts secured with safety wire, nuts safety wired <b>or</b> self-locking <b>and</b> siliconed	
Fork oil drain bolts safety wired <b>or</b> taped with duct tape <b>or</b> siliconed	
<b>Swing arm</b>	
Axle nut secured with safety wire or cotter pin. Reusable cotter pins must be safety wired	
<b>Wheels/Tires</b>	
Straight cast wheels	
No loose or broken spokes on wire spoke wheels	
Acceptable tread depth where applicable (must <b>not</b> be less than wearbars)	
Metal valve caps	
<b>Bodywork/Exhaust</b>	
All bodywork and exhaust headers and pipes must be securely fastened to the bike	
No sharp or broken edges which could result in injury	
All <b>stands</b> removed. <b>Kick start levers</b> either removed or secured with cable tie or safety wire	
<b>Drive chain</b>	
Chain master links <b>must be</b> safety wired	
<b>Rider Equipment</b>	
Helmet: <b>Snell 2000</b> , ECE 22-04, ECE 22-05 (P or J), JIST 8133:2003, BS 6658 Grade A	
Serviceable leathers (no holes or tears), Either one or two piece, must zip together at the waist	
Kidney belt, back protector	
Serviceable boots and gloves (no holes or tears) at least 8" high	