



## EMRA Tech Checklist

**Note: Fairing lowers must be removed Prior to Technical Inspection. NO Exceptions**

### Fluids Note: The use of antifreeze is strictly prohibited

- All drain plugs and filler caps (except fuel cap) safety wired
- Oil filter bolt safety wired, oil filter cans safety wired or clamped and wired
- Vent and overflow tubes routed into catch can
- Brake (and clutch if applicable) master cylinder taped or wrapped with terry cloth

### Brakes

- Banjo bolts safety wired or siliconed
- Caliper mounting bolts and/or nuts safety wired
- Test lever travel front and rear
- Front brake lever bolt safety wired or siliconed or secure with castellated nut and cotter pin
- Front brake lever guard

### Front forks

- Axle nut secured with safety wire or cotter pin
- Axle pinch bolts secure with safety wire, nuts safety wired or self locking and siliconed
- Appropriate engine protection with race specific case covers and/or frame savers

### Electrical

- Functioning kill switch

### Swingarm

- Axle nut secured with safety wire or cotter pin. Reusable cotter pins must be safety wired
- Rear sprocket guard (Shark guard) - no access for limbs between swingarm, lower chain and rear sprocket

### Wheels/Tires

- No loose or broken spokes on wire spoke wheels
- Acceptable tread depth where applicable (not less than wear bars)
- Metal valve stem caps

### Bodywork/Exhaust

- All bodywork and exhaust headers and pipes must be securely fastened to the bike
- Lower fairing is sealed and free of holes/cracks
- No sharp or broken edges that could result in injury
- Regulation size and colour for race numbers (legibility is key)
- All stands removed. Kick start levers either removed or secured with safety wire or cable tie

### Drive chain

- Clip style master links **must be** safety wired and oriented in the proper direction

### Rider equipment

- Helmet Snell M2010 or M2015, ECE 22.05 P, BSI 6658 Type A, JIS 8133:2007 all qualify if in good condition unaltered, and within 5 years to the month manufacture date. GoPro/Camera mounts are disallowed
- Leathers one or two piece (must zip together at waist) in serviceable condition, no holes or tears
- Separate race style back protector or suitable protector built into suit, thin foam pads are not acceptable
- Serviceable boots (at least 8" high) and gauntlet style gloves, no holes or tears
- Medical Data Carrier on lower right side of helmet

**BIKE # :** \_\_\_\_\_ **Red** \_\_\_\_\_ **Black** \_\_\_\_\_ **Tech Completed by:** \_\_\_\_\_



## EMRA Tech Checklist