

Tech Checklist

Bike #: _____ Red: _____ Black: _____ Tech Completed by: _____

<input checked="" type="checkbox"/>	Fluids
	All drain plugs and filler caps (except fuel cap) safety wired
	Oil filter bolt/cap safety wired, oil filter cans safety wired or clamped and wired
	Vent and overflow tubes routed into catch can
	Brake (and clutch if applicable) master cylinder reservoir taped or wrapped with terry cloth
	No fluid leaks
<input checked="" type="checkbox"/>	Brakes
	Banjo bolts safety wired or silicone
	Caliper mounting bolts and/or nuts safety wired
	Test lever travel front and rear
	Front brake lever bolt safety wired or silicone or secure with castellated nut and cotter pin
	Front brake lever guard
	Brake fluid level between min and max level indicator
<input checked="" type="checkbox"/>	Throttle
	Throttle must snap shut when released and at all steering angles
<input checked="" type="checkbox"/>	Front Forks
	Axle nut secured with safety wire or cotter pin
	Axle pinch bolts secure with safety wire, nuts safety wired or self locking and silicone
	Appropriate engine protection with race specific case covers and/or frame savers
<input checked="" type="checkbox"/>	Electrical
	Functioning kill switch
<input checked="" type="checkbox"/>	Swingarm
	Axle nut secured with safety wire or cotter pin. Reusable cotter pins must be safety wired
	Rear sprocket guard (Shark Guard)
<input checked="" type="checkbox"/>	Wheels/Tires
	No loose or broken spokes on wire spoke wheels
	Acceptable tread depth where applicable (not less than wear bars)
	Metal valve stem caps
<input checked="" type="checkbox"/>	Bodywork/Exhaust
	All bodywork and exhaust headers and pipes must be securely fastened to the bike
	Lower fairing is sealed and free of holes/cracks
	No sharp or broken edges that could result in injury
	Regulation size and color for race numbers (legibility is key)
	All stands removed. Kick start levers either removed or secured with safety wire or cable tie
<input checked="" type="checkbox"/>	Drive Chain
	Clip style master links must be safety wired and oriented in the proper direction
<input checked="" type="checkbox"/>	Rider Equipment
	Helmet – Snell M2015 or M2020D/R, ECE 22.05 P, BS 6658 Type A, JIS 8133:2007, FRHPhe-01 – Less than 5 years to the manufacturing month date, Go-pro/Camera mounts are disallowed
	Leathers – 1 or 2 pc (must zip together at waist) – no holes or rips and in good condition
	Back protector – Separate or built-in – Thin foam pads are not acceptable
	Boots – 8" high
	Gloves – Gauntlet Style with no holes or tears
	Medical Data Carrier
	Air Bag Vest (if applicable) – Alpinestars TechAir (6508016, 6508222, 6508020, 6508120), Dainese D-Air Racing 1 Piloti, (Racer to prove FIM acceptable)